

MARINE GENERATOR SPECIFICATIONS



KOHLER[®]
IN POWER. SINCE 1920.

Generator Model	kW*	Hz	Cylinder	RPM	Phase	Voltage	Amps	Length x Width x Height mm (in)		Weight (Wet) kg (lb)			
								H - Housed / U - Unhoused / R - Radiator					
40EOZDJ	40	60	4	1800	3	120 / 208	139	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1524 (60) x 722 (28.4) x 960 (37.8) R - 1858 (73.2) x 827 (32.6) x 1265 (49.8)	H - 1025 (2260) U - 935 (2060) R - 957 (2110)*				
						120 / 240	120						
						1	120 / 240			150			
33EFOZDJ	33	50			1500	3	127 / 220			131			
							139 / 240			120			
							277 / 480			60			
40EFOZDJ	40	50	4	1500	3	110 / 190	125	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1549 (60.9) x 738 (29) x 961 (37.8) R - 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H - 1080 (2380) U - 971 (2140) R - 993 (2190)*				
						110 / 220	108						
						1	115 / 230			143			
50EFOZDJ	50	50			4	1500	3			220 / 380	63	H - 1690 (66.5) x 767 (30.2) x 1015 (39.9) U - 1606 (63.2) x 738 (29) x 961 (37.8) R - 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H - 1114 (2456) U - 1005 (2216) R - 1028 (2266)*
										230 / 400	60		
										240 / 416	57		
55EOZDJ	55	60	4	1800			3	110 / 190	190	H - 1633 (64.3) x 767 (30.2) x 1015 (39.9) U - 1549 (60.9) x 738 (29) x 961 (37.8) R - 1884 (74.2) x 827 (32.5) x 1265 (49.8)	H - 1090 (2404) U - 982 (2164) R - 1004 (2214)*		
								120 / 208	191				
								1	120 / 240				
45EFOZDJ	45	50			4	1500	3	127 / 220	180			H - 1690 (66.5) x 767 (30.2) x 1015 (39.9) U - 1606 (63.2) x 738 (29) x 961 (37.8) R - 1941 (76.4) x 827 (32.5) x 1265 (49.8)	H - 1125 (2480) U - 1016 (2240) R - 1039 (2290)*
								139 / 240	165				
								277 / 480	83				
65EOZDJ	65	60	4	1800			3	110 / 190	171	H - 1754 (69) x 831 (32.7) x 1032 (40.6) U - 1657 (65.2) x 753 (29.6) x 999 (39.3) R - 1992 (78.4) x 890 (35) x 1277 (50.2)	H - 1270 (2800) U - 1148 (2530) R - 1179 (2600)*		
								110 / 220	148				
								1	115 / 230				
55EFOZDJ	55	50			4	1500	3	220 / 380	95			H - 1829 (72) x 831 (32.7) x 1032 (40.6) U - 1732 (68.2) x 753 (29.6) x 999 (39.3) R - 2067 (81.3) x 890 (35) x 1277 (50.2)	H - 1356 (2990) U - 1243 (2740) R - 1275 (2810)*
								230 / 400	90				
								240 / 416	87				
80EOZDJ	80	60	4	1800			3	120 / 208	278	H - 2205 (86.8) x 971 (38.2) x 1065 (41.9) U - 2091 (82.3) x 893 (35.2) x 1003 (39.5) R - 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H - 1683 (3710) U - 1515 (3340) R - 1578 (3478)		
								120 / 240	241				
								1	120 / 240				
70EFOZDJ	70	50			4	1500	3	127 / 220	262			H - 2205 (86.8) x 971 (38.2) x 1065 (41.9) U - 2091 (82.3) x 893 (35.2) x 1003 (39.5) R - 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H - 1719 (3789) U - 1551 (3419) R - 1613 (3557)
								139 / 240	241				
								277 / 480	120				
99EOZDJ	99	60	4	1800			3	110 / 190	266	H - 2205 (86.8) x 971 (38.2) x 1065 (41.9) U - 2091 (82.3) x 893 (35.2) x 1003 (39.5) R - 2466 (97.1) x 1129 (44.5) x 1275 (50.2)	H - 2147 (4733) U - 2067 (4558)		
								110 / 220	230				
								1	115 / 230				
80EFOZDJ	80	50			4	1500	3	220 / 380	105			H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)
								230 / 400	95				
								240 / 416	89				
125EOZDJ	125	60	6	1800			3	120 / 208	434	H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)		
								120 / 240	376				
								1	127 / 220				
100EFOZDJ	100	50			6	1500	3	127 / 220	410			H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)
								139 / 240	376				
								277 / 480	188				
150EOZDJ	150	60	6	1800			3	110 / 190	380	H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)		
								120 / 208	347				
								1	110 / 220				
125EFOZDJ	125	50			6	1500	3	220 / 380	190			H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)
								230 / 400	180				
								240 / 416	173				
200EOZDJ	200	60	6	1800			3	120 / 208	520	H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)		
								120 / 240	601				
								1	127 / 220				
175EFOZDJ	175	50			6	1500	3	139 / 240	451			H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)
								277 / 480	226				
								110 / 190	474				
200EFOZDJ	200	60	6	1800			3	120 / 208	694	H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)		
								120 / 240	601				
								1	127 / 220				
175EFOZDJ	175	50			6	1500	3	139 / 240	601			H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)
								277 / 480	301				
								110 / 190	665				
175EFOZDJ	175	50	6	1500			3	110 / 220	574	H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)		
								120 / 208	607				
								220 / 380	332				
175EFOZDJ	175	50			6	1500	3	230 / 400	316			H - 2661 (104.8) x 1048 (41.3) x 1174 (46.2) U - 2490 (98) x 970 (38.2) x 1086 (42.8)	H - 2147 (4733) U - 2067 (4558)
								240 / 416	304				
								240 / 416	304				

DIESEL

*kW rating varies by voltage. Consult the generator spec sheet for more detail.

AMERICAS/CARIBBEAN
+1 920-565-3381
+1 800-544-2444
Fax 920-459-1646

CHINA
+86 21 26062169
+86 400 1808 900

**EUROPE
MIDDLE EAST
AFRICA**
+31 168 331630

ASIA PACIFIC
+65 6264 6422
Fax +65 6264 6455

INDIA
+91 80 42867000
+91 80 23615972

KOHLERPOWER.COM

Printed in U.S.A. G12-479 1/17 © 2017 by Kohler Co.